

Double-Sided Garden Flag Layout

Sketch, measure and align both faces before you print.

Blank brand / SKU: _____

Overall W x H (in): _____

Flag construction: _____

Rod pocket depth (in): _____

FRONT + BACK DESIGN MAP A / STREET-FACING SIDE

NOT TO SCALE - MEASURE YOUR BLANK B / REVERSE SIDE

ROD POCKET / SEAM

Keep design clear unless approved

SKETCH / SAFE PRINT AREA

Turn over
→
after cooling

ROD POCKET / SEAM

Keep design clear unless approved

SKETCH / SAFE PRINT AREA

WRITE YOUR EXACT ALIGNMENT REFERENCES

Printable W x H (in): _____

Edge / seam clearance (in): _____

Front design top + left (in): _____

Back design top + left (in): _____

☐ Front transfer mirrored

☐ Back transfer mirrored

☐ Text reads correctly

Important

These frames are layout sketches, not full-size cutting templates. The actual printable area depends on the rod pocket, stitching and the blank supplier. A single-sided flag may not accept independent designs on both faces.

Double-Sided Press + Test Log

Record the exact supplier settings for each side. Never mix settings from different blanks.

Supplier / SKU: _____

Press model: _____

Fabric / layers: _____

Ink + paper: _____

TEST FIELD	SIDE A / FRONT	SIDE B / BACK
Artwork / transfer file	_____	_____
Transfer print size (in)	_____	_____
Mirrored? Yes / No	_____	_____
Temperature (supplier)	_____	_____
Time + pressure (supplier)	_____	_____
Protective sheets / setup	_____	_____
Tape + print orientation	_____	_____
Cooling + paper removal	_____	_____

CHECK BEFORE EACH PRESS

- ☐ Exact blank confirmed double-sided
 ☐ Fresh protective sheet above transfer
- ☐ Rod-pocket + seams outside design
 ☐ Blank supplier settings followed
- ☐ Transfer mirrored and secured
 ☐ First side cooled before side B
- ☐ Fresh protective sheet under flag
 ☐ Inspect both sides after final press

OUTCOME / CHANGES FOR NEXT TEST

Side A: _____

Side B: _____

SUPPLIER EXAMPLES - NOT UNIVERSAL SETTINGS

HeatPressNation: 385°F / 50 sec / medium pressure on its polyester flag example.

Artesprix: 400°F / 55 sec in a Halloween garden flag sublimation-marker project.

Twisted Ink 600D double-sided flag: 400°F / 70 sec / heavy pressure; cool before side B.

HeatPressNation **Artesprix** **Twisted Ink**